

## **General Disclaimer**

### **One or more of the Following Statements may affect this Document**

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

ON TRANSIT TIME INSTABILITY IN LIQUID JETS

G. Grabitz and G. Meier



Translation of 'Ueber Laufzeitinstabilitaeten in Fluessigkeitsstrahlen,'  
Max-Planck Institut fuer Stroemungsforschung, Goettingen (West Germany),  
Preprint Report, 1982, pp 1-6

(NASA-TM-77455) ON TRANSIT TIME INSTABILITY  
IN LIQUID JETS (National Aeronautics and  
Space Administration) 11 p HC A02/MF A01

CSSL 20D

N84-19742

Unclas  
12473

G3/34

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION  
WASHINGTON, D.C. 20546  
AUGUST 1982

ORIGINAL PAGE 19  
OF POOR QUALITY

STANDARD TITLE PAGE

1. Report No. NASA TM-77455	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle ON TRANSIT TIME INSTABILITY IN LIQUID JETS		5. Report Date	
		6. Performing Organization Code	
7. Author(s) G. Grabitz and G. Meier		8. Performing Organization Report No.	
		10. Work Unit No.	
9. Performing Organization Name and Address Leo Kanner Associates Redwood City, California 94063		11. Contract or Grant No. NASw-3199	
		13. Type of Report and Period Covered Translation	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration, Washington, D.C. 20546		14. Sponsoring Agency Code	
15. Supplementary Notes Translation of "Uber Laufzeitinstabilitaeten in Fluessigkeitsstrahlen", Max-Planck Institut fuer Stroemungsforschung, Goettingen (West Germany), Reprint Report, 1982, pp 1-6			
16. Abstract  The purpose of the study is to find a basic transit time instability in flows with disturbances of speed. It was shown that the mass distribution is established by and large by the described transit time effects. These transit time effects may also be involved for gas jets.			
17. Key Words (Selected by Author(s))		18. Distribution Statement  Unlimited-Unclassified	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 9	22. Price

# ON TRANSIT TIME INSTABILITY IN LIQUID JETS

G. Grabitz and G. Meier

Important aspects of the disintegration of liquid jets can be explained simply by transit time effects. But such phenomena certainly play a role in all velocity modulated flows. To discuss this situation we will first indicate here an exact solution of the differential equations of flow. By comparing this theoretical result with our own water jet experiments we will then show that a relationship can be produced with the stability of the jet. /1\*

## Theory of the Monodimensional Liquid Jet

We are considering here the liquid jet in the field of gravity (earth's acceleration  $g$ ) of a friction free, monodimensional, unstationary problem without surface tension. The pressure in the jet is superimposed by the external pressure. Thus the velocity components  $u(x,t)$ ,  $v(x,t)$  and the cross-section area  $F(x,t)$  are the flow quantities determining the jet (compare Figure 1). The time is designated as  $t$ , the  $x$ -coordinate is in the direction of the speed of outflow  $u_A(t)$  from the nozzle. The angle gives the slope of the  $x$ -axis against the horizontal. The equations of conservation of mass and momentum are

$$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} = -g \sin \gamma$$

$$\frac{\partial v}{\partial t} + u \frac{\partial v}{\partial x} = -g \cos \gamma$$

$$\frac{\partial F}{\partial t} + u \frac{\partial F}{\partial x} + F \frac{\partial u}{\partial x} = 0$$

with the pregiven values for  $x=0$ ;  $u=u_A(t)$ ,  $v=0$  and  $F=F_A$ . /2

\*Numbers in the margin indicate pagination in foreign text.

By introducing the Lagrange coordinates according to

$$\begin{aligned} t(\psi, \tau) &= \psi, \\ X(\psi, \tau) &= u_A(\tau) (\psi - \tau) - \frac{g \sin \gamma}{2} (\psi - \tau)^2 \end{aligned}$$

our basic equations are greatly simplified:

$$\begin{aligned} \frac{\partial u}{\partial \psi} &= -g \sin \gamma, \\ \frac{\partial v}{\partial \psi} &= -g \cos \gamma, \\ \frac{\partial F}{\partial \psi} &= F \frac{\frac{du_A}{d\tau} + g \sin \gamma}{u - \frac{du_A}{d\tau} (\psi - \tau)}. \end{aligned}$$

The pregiven values are now  $\psi = \tau$ :  $u = u_A(\tau)$ ,  $v = 0$ ,  $F = F_A$ .

We derive them easily in the form of an exact solution the flow quantities as a function of the actual time  $\psi$  and the time  $\tau$  at which the flow particles leave the nozzle with the initial velocity  $u_A(\tau)$ :

$$\begin{aligned} u(\psi, \tau) &= u_A(\tau) - g \sin \gamma (\psi - \tau), \\ v(\psi, \tau) &= -g \cos \gamma (\psi - \tau), \end{aligned}$$

$$F(\psi, \tau) = \left| \frac{F_A u_A(\tau)}{u_A(\tau) - \left[ g \sin \gamma + \frac{du_A}{d\tau} \right] (\psi - \tau)} \right|.$$

As exam $\phi$ : we choose here for the time dependence of the speed on the nozzle a sinusoidal disturbance superimposed on the constant basic velocity  $\bar{u}$ : /3

$$u_A(\tau) = \bar{u} (1 + \varepsilon \sin(\omega \tau))$$

and introduce the nondimensional time  $\hat{\tau} = \tau \bar{u} / RA$  ( $RA = \sqrt{FA/\pi}$ ). In our solution

$$\frac{F}{F_A} = \frac{1 + \varepsilon \sin(\Omega \hat{\tau})}{|1 + \varepsilon \sin(\Omega \hat{\tau}) + [G - \varepsilon \Omega \cos(\Omega \hat{\tau})](\hat{v} - \hat{\tau})|}$$

three nondimensional parameters occur with the interference of velocity  $\varepsilon$ , the Froude number  $G = gRA \sin \theta / \bar{u}^2$  and the Strouhal number  $\Omega = \omega$  by  $RA/\bar{u}$ . If the disturbance  $\varepsilon > G/\Omega$  then the solution has points of infinity. From the point  $x=0$  (that is  $\hat{v} = \hat{\tau}$ ) before the first infinity point at periodical distances with the running length increasing maxima of the jet cross-section arise. After the first infinity point the x-axis is covered in a multiple way by flow material. Before we can achieve by comparison with the experiments the physical explanation of this situation, it may be established here that the mass collection in the jet in accordance with the hypotheses of our theory can arise only by collection or overtaking processes of the liquid particles of the jet, since interactions of the particles with each other are not taken into consideration.

For  $\varepsilon < G/\Omega$  the disturbances of the jet are damped. In quantities with dimensions, the corresponding conditions for the speed disturbance is  $\delta u < g/\omega$ .

#### Experiments with Water Jet and Comparison with Theory

/4

A schematic representation of the experimental plant is given in Figure 2. The tube which can swivel around the longitudinal axis (internal diameter 25 mm) of the jet equipment has an inlet from a pump through a throttle resistance and an outlet through a nozzle (internal diameter 3 mm). The flow can be perturbed by a piston at the end of the tube with a pre-given frequency. The measurement of the perturbing amplitude takes place through a pressure convertor which is also applied laterally on the tube. Figure 3 shows a flashlight photo of a jet flowing out horizontally. Below it gives the corrected variation for the same frequency (Strouhal number 0.15) and the same disturbance ( $\varepsilon = 5.5\%$ ) for approximately the

same phase position of the disturbance. The low curve represents the cross-section area. This curve is partly doubly covered. The peaks correspond each time to the reversal edges of the undulating course of the jet shown above. In the experiment the exchange of momentum and surface tension in an early study caused the formation of the drop which lies in the doubly covered region between the two peaks of the mass collections and continues as a rigid body (held together by the surface tension). The residual flow material which was not connected in the drop is arranged in accordance with the theoretical curve.

Figure 4 shows a comparison of theory and experiment for the jet directed upwards in a vertical direction. The jet is somewhat inclined in the experiment in order that the material falling back flows away laterally. The disturbance increases in a very similar way in the theory and experiment. Whereas according to our simple theory a double covering occurs, in the experiment there is a tearing away of the jet. Here the surface tension is certainly involved, but this tearing can be understood even with the change of momentum. In the region of the double covering an average speed arises and therefore a discontinuity of speed with regard to the neighboring particles in which there is no double covering. A forwards jump in speed means practically the breaking away of the jet. /5

Figure 5 shows the comparison of the theory and experiment for the jet directed vertically downwards (water cock). The Strouhal number is 0.54 and the disturbance is speed is here 1.1 %. This picture may be used as illustration of our stability findings for the jet directed vertically downwards: here too the smallest perturbation is excited if only the perturbing frequency is high enough.


## Summary

The purpose of this study is to discover a basic transit time instability in flows with disturbances of speed. The impression should not be

/6

**Address:**

Dr. G. Grabitz and Dr. G. Meier, Max-Planck Institute for Flow Research,  
Boettinger Str. 4-8, D-3400 Goettingen.



### Figure 1: Notations



ORIGINAL PAGE IS  
OF POOR QUALITY




Figure 2: Schematic representation of the experimental plant.

Key: (1) inlet; (2) nozzle;  
(3) pressure transducer;  
(4) piston.




Figure 3: Water jet flowing out horizontally with perturbed initial speed (frequency 40 hz, amplitude 5.5 percent). Top: flashlight photo; Center: calculated variation; Bottom: cross-section of the beam.

ORIGINAL PAGE IS  
OF POOR QUALITY





Figure 4: Water jet flowing out upwards with disturbed initial velocity (frequency 40 Hz, amplitude 2.7 percent). Flashlight photo and calculated jet (with rotation symmetry).



$$\varepsilon = 0,011$$

$$f = 160 \text{ Hz}$$

$$(\Omega = 0,54)$$

$$u_A = 2,8 \text{ m/s}$$

Figure 5: Water jet flowing downwards vertically with disturbed initial velocity (frequency 116 Hz, amplitude 1.1 percent). Flashlight photo and calculated jet (with rotation symmetry)